

LISN OVERVIEW



TBOH01



TBL0550-1



TBL5016-1



TBL50100-1



TBLC08



TBL5016-2



TBL5016-3 / TBL5032-3

Model	TBOH01	TBL0550-1	TBL5016-1	TBL50100-1	TBLC08	TBL5016-2	TBL5016-3	TBL5032-3
Impedance	5 μ H // 50 Ω	5 μ H // 50 Ω	50 μ H // 50 Ω	50 μ H // 50 Ω	(50 μ H+5 Ω)// 50 Ω	(50 μ H+5 Ω)// 50 Ω	(50 μ H+5 Ω)// 50 Ω	(50 μ H+5 Ω)// 50 Ω
Frequency range	150 kHz – 108 MHz	150 kHz – 108 MHz	150 kHz – 30 MHz	150 kHz – 30 MHz	9 kHz – 30 MHz	9 kHz – 30 MHz	9 kHz – 30 MHz	9 kHz – 30 MHz
Path	1	1	1	1	2	2	3	3
Max. current	10 A	50 A	16 A	100 A	8 A	16 A	16 A	32 A
Max. Voltage	60V nominal, Component rating: 250V	60V nominal, Component rating: 250V	250V	250V	240V	240V	540V/260V	540V/260V
EUT Socket	4mm (banana)	Phoenix High current	Phoenix High current	Phoenix Hochstrom	Country specific mains socket	Country specific mains socket	CEE/IEC60309	CEE/IEC60309
Additional Features					Filter / Limiter / Attenuator, switchable Artificial hand connection PE switchable: 50 Ω // 50 μ H	Filter / Limiter / Attenuator, switchable Artificial hand connection PE switchable: 50 Ω // 50 μ H	Artificial hand connection PE switchable: 50 Ω // 50 μ H	Artificial hand connection PE switchable: 50 Ω // 50 μ H